

CIS CHEM FLOW -112

HIGH WATER REDUCING ADMIXTURE

PRODUCT CATEGORY: NAPHTHALENE BASED ADMIXTURE

PRODUCT DESCRIPTION

CIS CHEM FLOW 112 IS SNF based super plasticizing admixture having water reduction capacity up to 20% for structural concrete PQC

Great effect in dispersion even in mixes with high fines high workability for longer periods lower pumping pressure resistance to sagrigation even at high workability extended setting with longer workability reduces wate content for a given workability can be achive 26 – 28% water reduction with optium dosage of admixture reduce rate of workability loss normally associated with super plasticizer reduces shrinking cracking because of lower water content ratio makes the concrete water imermable higher ultimate strength incresed ease in finishing concrete

USES

CIS CHEM FLOW 112 facilitates excellent water reduction, with optimum cohesion and workability as required, just by adjusting the dosage. It is used mainly to the following types of concrete:

- Precast concrete structures in general
- Precast concrete tunnel segments
- Pre-stressed concrete elements
- Post-tensioned concrete bridge segments
- Piles, foundations, retaining walls etc.
- Concrete with high water reduction that requires high workability, slump retention along with high early strength development
- Blocks and Interlocks

CHARACTERISTICS / ADVANTAGES

CIS CHEM FLOW 112 SNF based super plasticizer admixture having water retention capacity up to 20%

. CIS CHEM FLOW 112 provides the following beneficial properties:

- Increased working time Early strength development resulting in economic stripping time for pre-cast and in cast-situe concrete
- High water reduction resulting in high density, high strength and reduced water permeability
- Excellent plasticizing effect giving improved flowability, placing and compaction behavior
- Improved surface finish
- Better shrinkage and creep behaviour
- Low risk of segregation Reduces energy costs for steam cured pre-cast elements
- Does not contain chlorides or other steel corrosion promoting ingredient
- to produce pumpable concrete
- Better Slump Retention, to achieve pumpable concrete. Compatible with all types of cement.



CIS CHEM FLOW -112

HIGH WATER REDUCING ADMIXTURE

PRODUCT CATEGORY: NAPHTHALENE BASED ADMIXTURE

PRODUCT INFORMATION

Composition	Modified Naphthalene Formaldehyde Sulphonate
Packaging	250 KG
Appearance / Colour	Light brown to brown liquid
Shelf life	12 months from date of production if stored properly
Storage conditions	Store in undamaged, unopened, original sealed packaging in dry conditions at temperatures between +5 °C and +45 °C. Protect from direct sunlight and frost
Density	1.22 ± 0.05 kg/l at 30 °C
Total chloride ion content	Nil (EN 934-2)
Concreting guidance	The standard rules of good concreting practice for production and placing must be observed when using CIS CHEM FLOW 112 in concrete. Refer to relevant standards. Fresh concrete must be cured properly especially at high temperatures in order to prevent plastic and drying

APPLICATION INFORMATION

Recommended dosage	0.4 - 2.0 % by weight of binder Higher dosages by weight of binder can be used depending on the mix design, raw materials, climatic conditions and concrete requirements. Trial mixes must be performed to establish the exact dosage rate required.
Compatibility	CIS CHEM FLOW 112 may be combined with all types of Portland cement We recommend to perform trial mixes to establish the required performance when combined with the above products. Please consult our CIS Technical Department.

HEALTH AND SAFETY

CISCHEM FLOW 112 should not be swallowed or allowed to come into contact with skin and eyes. Suitable protective gloves and goggles should be worn. Splashes on the skin should be removed with water. In case of contact with eyes it shall be rinsed immediately with plenty of water and medical advice sought immediately. If swallowed, medical attention shall be sought immediately. Vomiting should not be used.