

CIS SHUTTERING P 600

MOULD RELEASEING AGENT

PRODUCT CATEGORY: DEMOULIND AGENT

PRODUCT DISCRIPTION

CIS SHUTTERING P 600 IS excellent de shuttering oil is specially formulated for construction industry. It is a careful blend of high performance based minral oils and additives with excellent de moulding chemicals. Further, these oils have optimum viscosity and prevent the formation of rust & sludge . We offer these shuttering oil in different quantity at industry leading prices.

APPLICATION

CIS SHUTTRING P 600 IS used straight from the drum and stirring or mixing is required . shuttering oil is applied by spraying gun, roller, brushes prior to pouring aerated concrete and is recommended for use as a concrete mould relase agent with the protection mould from rust

DILUTION OF CIS PSHUTTRING P 600

This is diluted with water in ratio of 1:4 (1 part of water based shuttring oil and 4 part of water)

This is very economical water based shuttring oil.this gives better coverage area due to less viscosity. we are lending manufacturer of high quality water based shuttring oil

BENEFITS

- Offers very good surface finish in concrete
- Excellent moulding relase characters
- Non toxic
- Increased wooden plank life / metal shutter life

COVRAGE

20-40 sq.mtrs /litr in ideal condition



CIS SHUTTERING P 600

MOULD RELEASEING AGENT

PRODUCT CATEGORY: DEMOULIND AGENT

SPECIFICATION

Viscosity @ 40c	20.0-24.0
Colour	Light brown to brown colour
Flash point ~c , min	160C
Pour point ~c ,min	-3